GATE SENTRY

EASILY DEPOLYED WHEN AND WHERE YOU NEED IT

The Gate Sentry offers superior mobility and flexibility. It is easily installed either temporarily or permanently where it's needed the most. You can move it when you want and where you want with easily modified technologies to match the requirements for each location.

Remote Management

Through network, wireless or hardwired communications, you are able to monitor and manage access to your site from anywhere in the world at any time by desktop, laptop, tablet or smart phone!

Sleek Design

The Gate Sentry can be customized to blend into the surroundings, or modified to serve as a deterrent to crime in the area.

Minimize Re-wiring

Accepts 90-277 VAC input and avoids traditional installation power obstacles and substantially reduces the cost of deploying our various technologies in ways not previously available.

Future Integration

Integration is huge among security experts, the Gate Sentry can be used as a standalone system or it can integrate with your current system. The Gate Sentry is also ready for future integration of additional technologies.

GATE SENTRY
SPECIFICATIONS

Options:

Communications
• Cellular, point to point, point to multi-point, mesh, Wi-Fi, GPS, fiber, copper

Cameras
• IP network, fixed, PTZ dome, HD1080p and megapixel on both fixed and PTZ, thermal, L.P.R. - multiple camera mounting configurations

Lighting
• LED flood lights, Raytec® IR illuminators, photoelectric Recording
• EDGE NVR camera-based, EDGE remote access, NVR software or remote recording through hardwire or wireless connectivity

Video Analytics
• Highly effective video analytics and video motion

Card Access Control
• Works with most reader manufacturers and software platforms

Optional Technology Devices
• Motion detection
• Access control
• LED flood lights
• WiFi access
• Video surveillance (multiple cameras and types)
• Two-way intercom
• IR illuminators
• Wireless gate operation
• Cellular communication
• Pre-recorded audio

Deterrents
• Red/Blue*, Amber/Blue, Amber/Clear LED strobe light, 2-way audio, sirens

Customizable**
• Custom colors, graphics, labeling, etc. are available upon request and/or by special order

*Red/Blue LED Strobes are for law enforcement use only
**Minimums required on certain custom features

Specifications:

Dimensions/Specs
• Pedestal tower: 9." X 9.0" X 129" high Base size: 20" X 20" X 2" high
• Plug-in 110 VAC power with optional battery charging
• Rugged aluminum structure
• Powder coated for durability

Power
• 110 VAC charge and lithium battery back-up
(variable battery pack sizes)

Power Input
• Accepts 90-277 VAC

Battery Back-Up Power
• High quality, long lasting and efficient lithium-ion based 3000 charge cycle battery packs
• Available in 45 Ah - 90 Ah - 135 Ah battery pack sizes

Solar Power (Optional)
• 60-150 watt solar package (requires limited 'powered technology' devices)

Remote System Status & Control
• Power Broker® dashboard system status monitoring platform

Mounting
• Heavy duty base system